


# SLP-385 V/1

## SPD - for low voltage / SPD type 2 / MOV

Surge arrester for TN and TT systems

pluggable module, visual fault signalling

- varistor surge arrester
- installation to LV installations, especially to sub-distribution boards
- for protection of the installations and equipments against impact of induced overvoltages during a lightning strike or switching overvoltages



Parameter name	Parameter value
Type of SPD	T2
Mounting	DIN rail 35 mm
Maximum operating voltage	$U_c$ 385.00 V AC
Maximum operating voltage	$U_c$ 500.00 V DC
Type of network	TN
Maximum overcurrent protection	160 A gL/gG
Short-circuit current rating	$I_{SCCR}$ 50.0 kA
Nominal discharge current (8/20 $\mu$ s)	$I_n$ 20.00 kA
Maximum discharge current (8/20 $\mu$ s)	$I_{max}$ 40.00 kA
Voltage protection level	$U_p$ 1.80 kV
Voltage protection level at 5 kA	$U_p$ 1.30 kV
Response time	$t_a$ 25 ns
TOV 120 min L-N	440 V
TOV characteristic (120 min)	withstand
Cross-section of connected conductors solid (min)	1.00 mm <sup>2</sup>

Cross-section of connected conductors solid (max)	<b>35.00 mm<sup>2</sup></b>
Cross-section of connected conductors stranded (min)	<b>1.00 mm<sup>2</sup></b>
Cross-section of connected conductors stranded (max)	<b>25.00 mm<sup>2</sup></b>
Fault indication	<b>red indication field</b>
Degree of protection	<b>IP 20</b>
Range of ambient temperatures (min/max)	<b>-40 / 80 °C</b>
Humidity	<b>5 - 95 %</b>
According to standard	<b>EN 61643-11:2012, IEC 61643-11:2011</b>
ETIM Class	<b>EC000941</b>
Plug module	<b>SLP-385 V/0</b>
Customs tariff number	<b>85363030</b>
EAN	<b>8595090519553</b>
Order number	<b>A01955</b>

SALTEK s.r.o., Dráždanská 561/85, 400 07 Ústí nad Labem, CZ | +420 475 655 511 | [info@saltek.cz](mailto:info@saltek.cz) | [www.saltek.eu](http://www.saltek.eu)

Technická podpora: 800 818 818 | [podpora@saltek.cz](mailto:podpora@saltek.cz)

20.05.2024 -

00:20:39