

FLP-ZP-7,5-VBH/3+1

SPD - for low voltage / SPD type 1 / 40 mm busbar system - T1+T2 (7,5 kA)


Combination of lightning current and surge arrester for systems TN and TT

pluggable module, visual fault signalling, module locking, onto 40 mm busbar system


- high performance lightning current arrester, installation at the boundary of zones LPZ 0 and LPZ 1 or higher, mainly to main distribution boards upstream power meters
- for protection against impact of direct or indirect lightning strikes in wide range of applications – houses, office or industrial buildings, resp. to sub- distribution boards in large buildings, for application in Germany



Product dimensions



Basic circuit diagram



Parameter name	Parameter value
Type of SPD	T1,T2,T3
Mounting	40 mm busbar system
Nominal voltage	U_n 230 V AC
Maximum operating voltage L-N	U_c 255.00 V AC
Maximum operating voltage N-PE	U_c 255.00 V AC
Type of network	TT TN-S
Maximum overcurrent protection	160 A gL/gG
Short-circuit current rating	I_{SCCR} 25.0 kA
Total discharge current (10/350 μ s)	$I_{Total(10/350)}$ 30.00 kA
Lightning impulse current (10/350 μ s) L-N	I_{imp} 7.50 kA
Lightning impulse current (10/350 μ s) N-PE	I_{imp} 50.00 kA
Nominal discharge current (8/20 μ s) L-N	I_n 20.00 kA
Nominal discharge current (8/20 μ s) N-PE	I_n 50.00 kA

Test voltage	U_{oc}	10.0 kV
Total discharge current (8/20 μ s)	$I_{Total(8/20)}$	100.00 kA
Maximum discharge current (8/20 μ s) L-N	I_{max}	60.00 kA
Maximum discharge current (8/20 μ s) N-PE	I_{max}	100.00 kA
Voltage protection level mode L-N	U_p	1.50 kV
Voltage protection level mode L-PE	U_p	1.50 kV
Voltage protection level mode N-PE	U_p	1.50 kV
Response time L-N	t_a	100 ns
Response time N-PE	t_a	100 ns
TOV 5 s L-N		335 V
TOV 5 s L-PE		440 V
TOV characteristic (TOV 5 s)		withstand
TOV 120 min L-N		440 V
TOV 120 min L-PE		335 V
TOV characteristic (120 min)		withstand
TOV 200 ms N-PE		1 200 V
TOV characteristic (TOV 200 ms)		withstand
Cross-section of connected conductors solid (min)		1.00 mm ²
Cross-section of connected conductors solid (max)		35.00 mm ²
Cross-section of connected conductors stranded (min)		1.00 mm ²
Cross-section of connected conductors stranded (max)		25.00 mm ²
Fault indication		red indication field
Degree of protection		IP 20
Range of ambient temperatures (min/max)		-40 / 80 °C
Humidity		5 - 95 %
According to standard		EN 61643-11:2012, IEC 61643-11:2011
ETIM Class		EC000381
Plug module		FLP-ZP-7,5-VBH/0
Customs tariff number		85363090
EAN		8595090566236
Order number		A06623

SALTEK s.r.o., Drážďanská 561/85, 400 07 Ústí nad Labem, CZ | +420 475 655 511 | info@saltek.cz |
www.saltek.eu
Technická podpora: 800 818 818 | podpora@saltek.cz

08.05.2024 -
16:33:36