

FLP-12,5-075-VH/1

SPD - for low voltage / SPD type 1 / MOV


Single-pole lightning current and surge arrester

pluggable module, visual fault signalling


- varistor lightning current arrester
- installation at the boundary of zones LPZ 0 and LPZ 1 or higher
- for protection against impact of partial lightning currents, induced overvoltages during a lightning strike or switching overvoltages



Product dimensions



Basic circuit diagram



Parameter name	Parameter value
Type of SPD	T1,T2
Mounting	DIN rail 35 mm
Nominal voltage	U_n 48÷60 V AC/DC
Maximum operating voltage	U_c 75.00 V AC
Maximum operating voltage	U_c 75.00 V DC
Type of network	TN
Maximum overcurrent protection	160 A gL/gG
Short-circuit current rating	I_{SCCR} 25.0 kA
Lightning impulse current (10/350 μ s)	I_{imp} 12.50 kA
Nominal discharge current (8/20 μ s)	I_n 20.00 kA
Maximum discharge current (8/20 μ s)	I_{max} 40.00 kA
Voltage protection level	U_p 0.45 kV
Response time	t_a 25 ns
Cross-section of connected conductors solid (min)	1.00 mm ²
Cross-section of connected conductors solid (max)	35.00 mm ²
Cross-section of connected conductors stranded (min)	1.00 mm ²

Cross-section of connected conductors stranded (max)	25.00 mm ²
Fault indication	red indication field
Degree of protection	IP 20
Range of ambient temperatures (min/max)	-40 / 80 °C
Humidity	5 - 95 %
According to standard	EN 61643-11:2012, IEC 61643-11:2011
ETIM Class	EC000381
Plug module	FLP-12,5-075-VH/0
Customs tariff number	85363030
EAN	8595090541684
Order number	A04168

SALTEK s.r.o., Drážďanská 561/85, 400 07 Ústí nad Labem, CZ | +420 475 655 511 | info@saltek.cz | www.saltek.eu

Technická podpora: 800 818 818 | podpora@saltek.cz

20.05.2026 -
23:34:29