DL-TLF-UHF

SPD - for data, signalling and telecommunications lines / ICT / Telecommunications


Two-stage surge protection for analog telephone line and xDSL

surge protection for analog telephone line and xDSL


- two-stage surge protection of analog telephone line and xDSL
- installation at boundary LPZ 0 - 1 and higher
- connection of metallic pair via screw terminals
- working voltage up to 170 V DC



Product dimensions



Basic circuit diagram



Parameter name		Parameter value
Type of SPD		D1,C2,C3
Location of SPD		ST 1+2+3
Mounting		DIN rail 35 mm
Maximum operating voltage	U_c	170.00 V DC
Serial resistance per core	R	10.00 Ω
Nominal load current	I_L	0.300 A
C2 nominal discharge current (8/20 µs) core-core	I_n	5.00 kA
D1 total discharge current (10/350 µs) cores-PE	I_{Total}	5.00 kA
C2 voltage protection level mode core-core (@Uoc/In)	U_p	600,00 V (10 kV / 5 kA)
C2 voltage protection level mode core-PE (@Uoc/In)	U_p	900,00 V (10 kV / 5 kA)
C3 voltage protection level mode core-core (@In - 1 kV/µs)	U_p	250,00 V (10 A)
C3 voltage protection level mode core-PE (@In - 1 kV/µs)	U_p	550,00 V (10 A)

Response time core-core	t_a	1 ns
Response time core-PE	t_a	100 ns
Treshold frequency core-core	f	150 MHz (@ –1 dB)
Insertion loss	A	<1 dB (@ 35 MHz)
Connection (input - output)		terminals-terminals
Degree of protection		IP 20
Range of ambient temperatures (min/max)		-40 / 70 °C
Humidity		5 - 95 %
According to standard		EN 61643-21+A1,A2:2013, IEC 61643-21+A1,A2:2012
ETIM Class		EC000943
Customs tariff number		85363010
EAN		8595090570844
Order number		A07084