DL-10G-PoE-IP66

SPD - for data, signalling and telecommunications lines / ICT / Ethernet and PoE - compact


Two-stage surge protection for outdoor Ethernet devices with PoE

surge protection for outdoor Ethernet devices with PoE


- two-stage Ethernet surge protection in combination with special PoE protection
- to protect Ethernet terminals with PoE (cameras, sensors, information panels, etc.)
- installation anywhere in the LPZ 0 zone
- for sale from 1.7.2022
- complies with all types of PoE/PoE+/PoE++ (according to IEEE 802.3 af/at/bt)



Product dimensions



Basic circuit diagram



Parameter name		Parameter value
Type of SPD		D1,C2,C3
Location of SPD		ST 1+2+3
Maximum operating voltage core-core	U_c	8,50 V DC
Maximum operating voltage pair-pair (POE)	U_c	58,00 V DC
Nominal load current per core at 25 °C	I_L	0.5 A
Treshold frequency core-core	f	500.00 MHz
Insertion attenuation at treshhold frequency		3.20 dB
C2 nominal discharge current (8/20 µs) core-core	I_n	0.15 kA
D1 total discharge current (10/350 µs) cores-PE	I_{Total}	2.00 kA
C2 total discharge current (8/20 µs) cores-PE	I_{Total}	10.00 kA
C2 voltage protection level mode core-core (@Uoc/In)	U_p	60,00 V (0,3 kV / 0,15 kA)
C2 voltage protection level mode core-PE (@Uoc/In)	U_p	700,00 V (2,5 kV / 1,25 kA)
C2 voltage protection level mode pair-pair (POE) (@Uoc/In)	U_p	90,00 V (0,3 kV / 0,15 kA)

C3 voltage protection level mode core-core (@In - 1 kV/µs)	U_p	45,00 V (10 A)
C3 voltage protection level mode core-PE (@In - 1 kV/µs)	U_p	500,00 V (10 A)
C3 voltage protection level mode pair-pair (POE) (@In - 1 kV/µs)	U_p	85,00 V (10 A)
Response time core-core	t_a	1 ns
Response time core-PE	t_a	100 ns
Connection (input - output)		RJ 45/RJ 45
Degree of protection		IP 66
Range of ambient temperatures (min/max)		-25 / 50 °C
Humidity		5 - 95 %
According to standard		EN 61643-21+A1,A2:2013, IEC 61643-21+A1,A2:2012
ETIM Class		EC000943
Customs tariff number		85363010
EAN		8595090570981
Order number		A07098