


# SLP-275-VB/3S+1

## SPD - for low voltage / SPD type 2 / Combination type

Combined type surge arrester for three-phase TN-S and TT systems

pluggable module, visual fault signalling, remote fault signalling

- combination of combined type surge arrester (serial combination varistor+GDT) and encapsulated spark gap, connected in the 3+1 mode
- installation to LV installations, especially to sub-distribution boards in areas with unstable grid voltage and where diesel generators are used, suitable also for measuring circuits
- for protection of the installations and equipments against impact of induced overvoltages during a lightning strike in areas with higher storm activity or switching overvoltages or as the first stage of for protection for measuring circuits
- zero leakage current



Parameter name	Parameter value
Type of SPD	T2
Mounting	DIN rail 35 mm
Nominal voltage	$U_n$ 230/400 V AC
Maximum operating voltage L-N	$U_c$ 275.00 V AC
Maximum operating voltage N-PE	$U_c$ 255.00 V AC
Type of network	TN-S TT
Maximum overcurrent protection	125 A gL/gG
Short-circuit current rating	$I_{SCCR}$ 50.0 kA
Residual current	$I_{PE}$ 0.002 mA
Nominal discharge current (8/20 $\mu$ s)	$I_n$ 20.00 kA
Maximum discharge current (8/20 $\mu$ s)	$I_{max}$ 40.00 kA
Voltage protection level mode L-N	$U_p$ 1.50 kV
Voltage protection level mode L-PE	$U_p$ 2.50 kV

Voltage protection level mode N-PE	$U_p$	1.50 kV
Ability to independently switch off the following current N-PE	$I_{fi}$	0.1 kA
Response time	$t_a$	100 ns
TOV 5 s L-N		335 V
TOV characteristic (TOV 5 s)		withstand
TOV 120 min L-N		440 V
TOV characteristic (120 min)		withstand
TOV 200 ms L-PE		1 455 V
TOV 200 ms N-PE		1 200 V
TOV characteristic (TOV 200 ms)		withstand
Cross-section of connected conductors solid (min)		1.00 mm <sup>2</sup>
Cross-section of connected conductors solid (max)		35.00 mm <sup>2</sup>
Cross-section of connected conductors stranded (min)		1.00 mm <sup>2</sup>
Cross-section of connected conductors stranded (max)		25.00 mm <sup>2</sup>
Cross-section of remote indication conductors solid (max)		1.5 mm <sup>2</sup>
Cross-section of remote indication conductors stranded (max)		1.5 mm <sup>2</sup>
Fault indication		red indication field
Remote indication		potential-free change-over contact
Remote indication contacts		250V/0,5A AC,250V/0,1A DC
Degree of protection		IP 20
Range of ambient temperatures (min/max)		-40 / 80 °C
Humidity		5 - 95 %
According to standard		EN 61643-11:2012, IEC 61643-11:2011
ETIM Class		EC000941
Plug module		SLP-275-VB/0 SLP-NPE V/0
Customs tariff number		85363030
EAN		8595090570608
Order number		A07060