FLP-B+C-MAXI-VSF/1

SPD - for low voltage / SPD type 1 / Combination type - T1 (25 kA)


Combination of lightning current and surge arrester with integrated backup fuse for systems TN and TT

pluggable module, visual fault signalling, module locking, remote fault signalling


- high performance lightning current arrester
- installation at the boundary of zones LPZ 0 and LPZ 1 or higher, mainly to main distribution boards
- for protection against impact of direct or indirect lightning strikes in wide range of applications – office or industrial buildings
- no follow current, zero leakage current
- with integrated backup fuse



Product dimensions



Basic circuit diagram



Parameter name		Parameter value
Type of SPD		T1,T2
Mounting		DIN rail 35 mm
Nominal voltage	U_n	230.00 V AC
Maximum operating voltage	U_c	260.00 V AC
Type of network		TN
Maximum overcurrent protection		-
Short-circuit current rating	I_{SCCR}	50.0 kA
Lightning impulse current (10/350 µs)	I_{imp}	25.00 kA
Nominal discharge current (8/20 µs)	I_n	30.00 kA
Voltage protection level	U_p	1.50 kV
Response time	t_a	100 ns
TOV 5 s L-N		335 V
TOV characteristic (TOV 5 s)		withstand
TOV 120 min L-N		440 V
TOV characteristic (120 min)		withstand

Cross-section of connected conductors solid (min)	2.50 mm^2
Cross-section of connected conductors solid (max)	50.00 mm^2
Cross-section of connected conductors stranded (min)	2.50 mm^2
Cross-section of connected conductors stranded (max)	35.00 mm^2
Cross-section of remote indication conductors solid (max)	1.5 mm^2
Cross-section of remote indication conductors stranded (max)	1.5 mm^2
Fault indication	red indication field
Remote indication	potential-free change-over contact
Remote indication contacts	250V/0,5A AC,250V/0,1A DC
Degree of protection	IP 20
Range of ambient temperatures (min/max)	-40 / 80 °C
Humidity	5 - 95 %
According to standard	EN 61643-11:2012, IEC 61643-11:2011
ETIM Class	EC001457
Plug module	FLP-B+C MAXI V/0
Customs tariff number	85363090
EAN	8595090571162
Order number	A07116