

SLP-150 V/4 S

SPD - for low voltage / SPD type 2 / MOV


Surge arrester for three-phases system TN-s (120/208 V AC)

pluggable module, visual fault signalling, remote fault signalling


- four-pole varistor surge arrester
- installation to LV installations, especially to sub-distribution boards in TN-S systems
- for protection of the installations and equipments against impact of induced overvoltages during a lightning strike or switching overvoltages



Product dimensions



Basic circuit diagram



| Parameter name | Parameter value |
|--|--------------------|
| Type of SPD | T2 |
| Mounting | DIN rail 35 mm |
| Nominal voltage | U_n 120.00 V AC |
| Maximum operating voltage | U_c 150.00 V AC |
| Maximum operating voltage | U_c 200.00 V DC |
| Type of network | TN-S |
| Maximum overcurrent protection | 160 A gL/gG |
| Short-circuit current rating | I_{SCCR} 50.0 kA |
| Residual current | I_{PE} 0.350 mA |
| Nominal discharge current (8/20 μ s) | I_n 15.00 kA |
| Maximum discharge current (8/20 μ s) | I_{max} 40.00 kA |
| Voltage protection level | U_p 0.74 kV |
| Voltage protection level at 5 kA | U_p 0.60 kV |
| Response time | t_a 25 ns |
| TOV 5 s L-N | 175 V |
| TOV characteristic (TOV 5 s) | withstand |

| | |
|--|-------------------------------------|
| Cross-section of connected conductors solid (min) | 4.00 mm ² |
| Cross-section of connected conductors solid (max) | 35.00 mm ² |
| Cross-section of connected conductors stranded (min) | 4.00 mm ² |
| Cross-section of connected conductors stranded (max) | 25.00 mm ² |
| Cross-section of remote indication conductors solid (max) | 1.5 mm ² |
| Cross-section of remote indication conductors stranded (max) | 1.5 mm ² |
| Fault indication | red indication field |
| Remote indication | potential-free change-over contact |
| Remote indication contacts | 250V/0,5A AC,250V/0,1A DC |
| Degree of protection | IP 20 |
| Range of ambient temperatures (min/max) | -40 / 80 °C |
| Humidity | 5 - 95 % |
| According to standard | EN 61643-11:2012, IEC 61643-11:2011 |
| ETIM Class | EC000941 |
| Plug module | SLP-150 V/0 |
| Customs tariff number | 85363030 |
| EAN | 8595090574507 |
| Order number | A07450 |