

# DM-006/1 4R DJ

## SPD - for data, signalling and telecommunications lines / I&C / ST2+3 (DM) - compact

Surge protection for 4-core signalling lines

coupling impedance (R – resistance)


- coarse and fine surge protection for 4-core signalling lines
- installation close to protected equipment
- for protection of communication interfaces of I&C, electronic security and fire detection systems, etc. (mainly for RS-485 interfaces) against impact of surge voltage
- coarse and fine surge protection in differential mode (core – core) and coarse protection in common mode (core – PE)



Product dimensions



Basic circuit diagram



Parameter name		Parameter value
Type of SPD		C2,C3
Location of SPD		ST 2+3
Mounting		DIN rail 35 mm
Nominal voltage	$U_n$	6.00 V DC
Maximum operating voltage	$U_c$	5.70 V AC
Maximum operating voltage	$U_c$	8.10 V DC
Nominal load current	$I_L$	0.060 A
Threshold frequency core-core	$f$	1.00 MHz
Serial resistance per core	$R$	6.80 $\Omega$
C2 nominal discharge current (8/20 $\mu$ s) per core	$I_n$	10.00 kA
C2 voltage protection level mode core-PE at $I_n$	$U_p$	350.00 V

C2 voltage protection level mode core-core at In	$U_p$	25.00 V
C3 voltage protection level mode core-PE at 1 kV/ $\mu$ s	$U_p$	650.00 V
C3 voltage protection level mode core-core at 1 kV/ $\mu$ s	$U_p$	12.00 V
Response time core-core	$t_a$	1 ns
Response time core-PE	$t_a$	100 ns
Connection (input - output)		terminals-terminals
Cross-section of connected conductors solid (max)		4.00 mm <sup>2</sup>
Cross-section of connected conductors stranded (max)		2.50 mm <sup>2</sup>
Degree of protection		IP 20
Range of ambient temperatures (min/max)		-40 / 80 °C
According to standard		EN 61643-21+A1,A2:2013, IEC 61643-21+A1,A2:2012
ETIM Class		EC001625
Customs tariff number		85363010
EAN		8595090516750
Order number		A01675