

SLP-275 V/3

SPD - for low voltage / SPD type 2 / MOV


Surge arrester for three-phase system TN-C

pluggable module, visual fault signalling, module locking


- three-pole varistor surge arrester
- installation to LV installations, especially to sub-distribution boards in TN-C systems
- for protection of the installations and equipments against impact of induced overvoltages during a lightning strike or switching overvoltages



Product dimensions



Basic circuit diagram



Parameter name	Parameter value
Type of SPD	T2
Mounting	DIN rail 35 mm
Nominal voltage	U_n 230.00 V AC
Maximum operating voltage	U_c 275.00 V AC
Maximum operating voltage	U_c 350.00 V DC
Type of network	TN
Maximum overcurrent protection	160 A gL/gG
Short-circuit current rating	I_{SCCR} 50.0 kA
Nominal discharge current (8/20 μ s)	I_n 20.00 kA
Maximum discharge current (8/20 μ s)	I_{max} 40.00 kA
Voltage protection level	U_p 1.35 kV
Voltage protection level at 5 kA	U_p 0.90 kV
Response time	t_a 25 ns
TOV 5 s L-N	335 V
TOV characteristic (TOV 5 s)	withstand
TOV 120 min L-N	440 V
TOV characteristic (120 min)	safe failure

Cross-section of connected conductors solid (min)	1.00 mm ²
Cross-section of connected conductors solid (max)	35.00 mm ²
Cross-section of connected conductors stranded (min)	1.00 mm ²
Cross-section of connected conductors stranded (max)	25.00 mm ²
Fault indication	red indication field
Degree of protection	IP 20
Range of ambient temperatures (min/max)	-40 / 80 °C
Humidity	5 - 95 %
According to standard	EN 61643-11:2012, IEC 61643-11:2011
ETIM Class	EC000941
Plug module	SLP-275 V/0
Customs tariff number	85363030
EAN	8595090517603
Order number	A01760

SALTEK s.r.o., Drážďanská 561/85, 400 07 Ústí nad Labem, CZ | +420 475 655 511 | info@saltek.cz | www.saltek.eu

Technická podpora: 800 818 818 | podpora@saltek.cz

14.05.2026 -
12:50:36