

SLP-075 VB/1 S

SPD - for low voltage / SPD type 2 / Combination type

Combined type surge arrester for TN and TT systems or signal lines

pluggable module, visual fault signalling, remote fault signalling

- combined type surge arrester (serial combination varistor+GDT)
- installation to LV installations, especially to sub-distribution boards, suitable also for measuring circuits
- for protection of the installations and equipments against impact of induced overvoltages during a lightning strike in areas with higher storm activity or switching overvoltages or as the first stage of protection for measuring circuits
- no leakage current



Product dimensions

Basic circuit diagram

Parameter name	Parameter value
Type of SPD	T2
Mounting	DIN rail 35 mm
Maximum operating voltage	U_c 75.00 V AC
Maximum operating voltage	U_c 100.00 V DC
Type of network	TN
Maximum overcurrent protection	125 A gL/gG
Short-circuit current rating	I_{SCCR} 35.0 kA
Nominal discharge current (8/20 μ s)	I_n 15.00 kA
Maximum discharge current (8/20 μ s)	I_{max} 25.00 kA
Voltage protection level	U_p 0.60 kV
Voltage protection level at 5 kA	U_p 0.30 kV
Response time	t_a 100 ns
Cross-section of connected conductors solid (min)	1.00 mm ²

Cross-section of connected conductors solid (max)	35.00 mm²
Cross-section of connected conductors stranded (min)	1.00 mm²
Cross-section of connected conductors stranded (max)	25.00 mm²
Cross-section of remote indication conductors solid (max)	1.5 mm²
Cross-section of remote indication conductors stranded (max)	1.5 mm²
Fault indication	red indication field
Remote indication	potential-free change-over contact
Remote indication contacts	250V/0,5A AC,250V/0,1A DC
Degree of protection	IP 20
Range of ambient temperatures (min/max)	-40 / 80 °C
Humidity	5 - 95 %
According to standard	EN 61643-11:2012, IEC 61643-11:2011
ETIM Class	EC000941
Plug module	SLP-075 VB/0
Customs tariff number	85363030
EAN	8595090521563
Order number	A02156