

# SLP-385 V/3 S

## SPD - for low voltage / SPD type 2 / MOV


Surge arrester for three-phase system TN with fluctuating voltage

pluggable module, visual fault signalling, module locking, remote fault signalling


- three-pole varistor surge arrester
- installation to LV installations, especially to sub-distribution boards in TN-C systems or TN-S without neutral conductor
- for protection of the installations and equipments against impact of induced overvoltages during a lightning strike or switching overvoltages
- for applications with fluctuating voltage



Product dimensions



Basic circuit diagram



Parameter name	Parameter value
Type of SPD	T2
Mounting	DIN rail 35 mm
Maximum operating voltage	$U_c$ 385.00 V AC
Maximum operating voltage	$U_c$ 500.00 V DC
Type of network	TN
Maximum overcurrent protection	160 A gL/gG
Short-circuit current rating	$I_{SCCR}$ 50.0 kA
Nominal discharge current (8/20 $\mu$ s)	$I_n$ 20.00 kA
Maximum discharge current (8/20 $\mu$ s)	$I_{max}$ 40.00 kA
Voltage protection level	$U_p$ 1.80 kV
Voltage protection level at 5 kA	$U_p$ 1.30 kV
Response time	$t_a$ 25 ns
TOV 120 min L-N	440 V
TOV characteristic (120 min)	withstand
Cross-section of connected conductors solid (min)	1.00 mm <sup>2</sup>

Cross-section of connected conductors solid (max)	35.00 mm <sup>2</sup>
Cross-section of connected conductors stranded (min)	1.00 mm <sup>2</sup>
Cross-section of connected conductors stranded (max)	25.00 mm <sup>2</sup>
Cross-section of remote indication conductors solid (max)	1.5 mm <sup>2</sup>
Cross-section of remote indication conductors stranded (max)	1.5 mm <sup>2</sup>
Fault indication	red indication field
Remote indication	potential-free change-over contact
Remote indication contacts	250V/0,5A AC,250V/0,1A DC
Degree of protection	IP 20
Range of ambient temperatures (min/max)	-40 / 80 °C
Humidity	5 - 95 %
According to standard	EN 61643-11:2012, IEC 61643-11:2011
ETIM Class	EC000941
Plug module	SLP-385 V/0
Customs tariff number	85363030
EAN	8595090526339
Order number	A02633