


# SLP-385 V/3 S

## SPD - for low voltage / SPD type 2 / MOV

Surge arrester for three-phase system TN with fluctuating voltage

pluggable module, visual fault signalling, module locking, remote fault signalling

- three-pole varistor surge arrester
- installation to LV installations, especially to sub-distribution boards in TN-C systems or TN-S without neutral conductor
- for protection of the installations and equipments against impact of induced overvoltages during a lightning strike or switching overvoltages
- for applications with fluctuating voltage



Parameter name	Parameter value
Type of SPD	T2
Mounting	DIN rail 35 mm
Maximum operating voltage	$U_c$ 385.00 V AC
Maximum operating voltage	$U_c$ 500.00 V DC
Type of network	TN
Maximum overcurrent protection	160 A gL/gG
Short-circuit current rating	$I_{SCCR}$ 50.0 kA
Nominal discharge current (8/20 $\mu$ s)	$I_n$ 20.00 kA
Maximum discharge current (8/20 $\mu$ s)	$I_{max}$ 40.00 kA
Voltage protection level	$U_p$ 1.80 kV
Voltage protection level at 5 kA	$U_p$ 1.30 kV
Response time	$t_a$ 25 ns
TOV 120 min L-N	440 V
TOV characteristic (120 min)	withstand
Cross-section of connected conductors solid (min)	1.00 mm <sup>2</sup>

Cross-section of connected conductors solid (max)	<b>35.00 mm<sup>2</sup></b>
Cross-section of connected conductors stranded (min)	<b>1.00 mm<sup>2</sup></b>
Cross-section of connected conductors stranded (max)	<b>25.00 mm<sup>2</sup></b>
Cross-section of remote indication conductors solid (max)	<b>1.5 mm<sup>2</sup></b>
Cross-section of remote indication conductors stranded (max)	<b>1.5 mm<sup>2</sup></b>
Fault indication	<b>red indication field</b>
Remote indication	<b>potential-free change-over contact</b>
Remote indication contacts	<b>250V/0,5A AC,250V/0,1A DC</b>
Degree of protection	<b>IP 20</b>
Range of ambient temperatures (min/max)	<b>-40 / 80 °C</b>
Humidity	<b>5 - 95 %</b>
According to standard	<b>EN 61643-11:2012, IEC 61643-11:2011</b>
ETIM Class	<b>EC000941</b>
Plug module	<b>SLP-385 V/0</b>
Customs tariff number	<b>85363030</b>
EAN	<b>8595090526339</b>
Order number	<b>A02633</b>