


DS-V130-RS

SPD - for data, signalling and telecommunications lines / I&C / Single stage SPD (DS)

Single stage surge arrester – Varistor

V – Varistor, screw terminals

- single stage surge arrester
- installation close to protected equipment
- for protection of signaling, data and other lines against impact of surge voltage



Parameter name		Parameter value
Type of SPD		C2
Location of SPD		ST 2
Mounting		DIN rail 35 mm
Maximum operating voltage	U_C	140.00 V AC
Maximum operating voltage	U_C	180.00 V DC
Nominal load current	I_L	16.000 A
C2 nominal discharge current (8/20 μ s) per core	I_n	6.00 kA
C2 voltage protection level mode core-PE at I_n	U_p	530.00 V
Response time core-PE	t_a	25 ns
Connection (input - output)		terminals-terminals
Cross-section of connected conductors solid (min)		0.14 mm ²
Cross-section of connected conductors solid (max)		4.00 mm ²
Cross-section of connected conductors stranded (min)		0.14 mm ²
Cross-section of connected conductors stranded (max)		2.50 mm ²
Range of ambient temperatures (min/max)		-40 / 70 °C

According to standard	EN 61643-21+A1,A2:2013, IEC 61643-21+A1,A2:2012
ETIM Class	EC000943
Customs tariff number	85363010
EAN	8595090551515
Order number	A05151

SALTEK s.r.o., Drážďanská 561/85, 400 07 Ústí nad Labem, CZ | +420 475 655 511 | info@saltek.cz | www.saltek.eu
Technická podpora: 800 818 818 | podpora@saltek.cz

16.06.2026 -
02:45:41