


ISGO-500H Ex

ISG - Isolating spark gaps / Ex environment


Isolation spark gap for Ex areas

connecting cable and M8 bolt with nut, stainless steel enclosure


- heavy duty encapsulated isolating spark gap for use in Hazardous (Ex) Areas II 2G Ex mb IIC T6 Gb and II 2D Ex mb IIIC T80 °C Db
- for indirect connection (earthing) of isolated conductive parts under lightning conditions
- for safe installation in Ex zone 1 (gas) or 21 (dust)



Product dimensions



Basic circuit diagram



Parameter name	Parameter value
Classification	class H - heavy duty
Isolation resistance	100.00 MΩ
Lightning impulse current	I_{imp} 100.00 kA
Rated impulse sparkover voltage	U_{imp} 1.50 kV
Rated power frequency withstand voltage	U_{WAC} 0.350 kV
Rated DC withstand voltage	U_{WDC} 0.500 kV
Degree of protection	IP 67
Range of ambient temperatures (min/max)	-40 / 50 °C
According to standard	EN 62561-3, EN 60079-0, EN 60079-18
Explosion-tested version	II 2G Ex mb IIC T6 Gb, II 2D Ex mb IIIC T80°C Db
ETIM Class	EC000510
Customs tariff number	85363090
EAN	8595090555148
Order number	A05514

SALTEK s.r.o., Drážďanská 561/85, 400 07 Ústí nad Labem, CZ | +420 475 655 511 | info@saltek.cz |
www.saltek.eu
Technická podpora: 800 818 818 | podpora@saltek.cz

16.06.2026 -
22:13:07