BDG-230-V/1-FR

SPD - for data, signalling and telecommunications lines / I&C / ST1+2+3 (BDM, BDG) - plugable


Lightning current arrester combined with fine surge protection for shielded 2-core signalling lines

pluggable module, coupling impedance (R – resistance), line separated from protective earth via GDT


- coarse and fine surge protection of shielded 2-core telecommunication, data and other lines
- coarse and fine surge protection (core – core) and coarse protection (core – GND) in differential mode, coarse surge protection in common mode (line – PE)
- installation at the boundary of LPZ 0 and LPZ 1 zones at the line entry into building
- for protection of telecommunication lines against impact of surge voltage



Product dimensions



Basic circuit diagram



Parameter name		Parameter value
Type of SPD		D1,C2
Location of SPD		ST 1+2+3
Mounting		DIN rail 35 mm
Nominal voltage	U_n	230.00 V DC
Maximum operating voltage	U_c	177.00 V AC
Maximum operating voltage	U_c	250.00 V DC
Nominal load current	I_L	0.500 A
Treshold frequency core-core	f	16.00 MHz
Serial resistance per core	R	3.30 Ω
D1 impulse discharge current (10/350 µs) per core	I_{imp}	2.50 kA
D1 total discharge current (10/350 µs) cores-PE	I_{Total}	5.00 kA

C2 nominal discharge current (8/20 µs) GND-PE	I_n	10.00 kA
C2 nominal discharge current (8/20 µs) per core	I_n	10.00 kA
C2 total discharge current (8/20 µs) cores-PE	I_{Total}	20.00 kA
C3 nominal discharge current (10/1000 µs) core-PE	I_{SM}	10.00 A
C3 nominal discharge current (10/1000 µs) core-core	I_{SM}	10.00 A
C3 voltage protection level mode GND-PE at 1 kV/µs	U_p	550.00 V
C3 voltage protection level mode core-GND at 1 kV/µs	U_p	550.00 V
C3 voltage protection level mode core-core at 1 kV/µs	U_p	350.00 V
Response time core-core	t_a	1 ns
Response time core-GND	t_a	100 ns
Response time GND-PE	t_a	100 ns
Connection (input - output)		terminals-terminals
Cross-section of connected conductors solid (min)		0.14 mm^2
Cross-section of connected conductors solid (max)		4.00 mm^2
Cross-section of connected conductors stranded (min)		0.14 mm^2
Cross-section of connected conductors stranded (max)		2.50 mm^2
Degree of protection		IP 20
Range of ambient temperatures (min/max)		-40 / 70 °C
According to standard		EN 61643-21+A1,A2:2013, IEC 61643-21+A1,A2:2012
ETIM Class		EC001466
Plug module		BDG-230-V/1-0
Customs tariff number		85363010
EAN		8595090557081
Order number		A05708