

# BDM-012-V/2-FR1

## SPD - for data, signalling and telecommunications lines / I&C / ST1+2+3 (BDM, BDG) - plugable


Lightning current arrester with coarse and fine surge protection for two 2-core

pluggable module, coupling impedance (R – resistance), line separated from protective earth via GDT


- lightning current arrester with coarse and fine surge protection for two 2-core signalling lines
- installation at the boundary of LPZ 0 and LPZ 1 zones or higher, at the line entry into building and also installation close to protected device
- for protection of telecommunication lines (version BDGHF-230) and interfaces of I&C, MaR systems, electronic security and fire detection systems, etc. (mainly for RS-485, PROFIBUS interfaces) against surge voltage
- coarse and fine surge protection (core – core, GND) in differential mode and coarse surge protection in common mode (line – PE)



Product dimensions



Basic circuit diagram



Parameter name	Parameter value
Type of SPD	<b>D1,C2</b>
Location of SPD	<b>ST 1+2+3</b>
Mounting	<b>DIN rail 35 mm</b>
Nominal voltage	$U_n$ <b>12.00 V DC</b>
Maximum operating voltage	$U_c$ <b>11.00 V AC</b>
Maximum operating voltage	$U_c$ <b>16.00 V DC</b>
Nominal load current	$I_L$ <b>1.000 A</b>
Threshold frequency core-core	$f$ <b>0.00 MHz</b>
Threshold frequency core-core	$f$ <b>2.00 MHz</b>
Serial resistance per core	$R$ <b>0.80 <math>\Omega</math></b>

Serial inductance per core	L	0.00 $\mu$ H
D1 impulse discharge current (10/350 $\mu$ s) per core	$I_{imp}$	2.50 kA
D1 total discharge current (10/350 $\mu$ s) cores-PE	$I_{Total}$	5.00 kA
C2 nominal discharge current (8/20 $\mu$ s) GND-PE	$I_n$	10.00 kA
C2 nominal discharge current (8/20 $\mu$ s) per core	$I_n$	10.00 kA
C2 total discharge current (8/20 $\mu$ s) cores-PE	$I_{Total}$	20.00 kA
C3 nominal discharge current (10/1000 $\mu$ s) core-PE	$I_{SM}$	10.00 A
C3 nominal discharge current (10/1000 $\mu$ s) core-core	$I_{SM}$	10.00 A
C3 voltage protection level mode GND-PE at 1 kV/ $\mu$ s	$U_p$	550.00 V
C3 voltage protection level mode core-GND at 1 kV/ $\mu$ s	$U_p$	22.00 V
C3 voltage protection level mode core-core at 1 kV/ $\mu$ s	$U_p$	22.00 V
Response time core-core	$t_a$	1 ns
Response time core-GND	$t_a$	1 ns
Response time GND-PE	$t_a$	100 ns
Connection (input - output)		terminals-terminals
Cross-section of connected conductors solid (min)		0.14 mm <sup>2</sup>
Cross-section of connected conductors solid (max)		4.00 mm <sup>2</sup>
Cross-section of connected conductors stranded (min)		0.14 mm <sup>2</sup>
Cross-section of connected conductors stranded (max)		2.50 mm <sup>2</sup>
Degree of protection		IP 20
Range of ambient temperatures (min/max)		-40 / 70 °C
According to standard		EN 61643-21+A1,A2:2013, IEC 61643-21+A1,A2:2012
ETIM Class		EC001625
Plug module		DM-012-V/2-0 BDM-012-V/2-0
Customs tariff number		85363010
EAN		8595090564010
Order number		A06401

SALTEK s.r.o., Drážďanská 561/85, 400 07 Ústí nad Labem, CZ | +420 475 655 511 | [info@saltek.cz](mailto:info@saltek.cz) |  
[www.saltek.eu](http://www.saltek.eu)  
*Technická podpora: 800 818 818 | [podpora@saltek.cz](mailto:podpora@saltek.cz)*

01.01.2026 -  
22:29:02