FLP-ZP-7,5-VBH/3

SPD - for low voltage / SPD type 1 / 40 mm busbar system - T1+T2 (7,5 kA)


Combination of lightning current and surge arrester for systems TN-C

pluggable module, visual fault signalling, module locking, onto 40 mm busbar system


- high performance lightning current arrester, installation at the boundary of zones LPZ 0 and LPZ 1 or higher, mainly to main distribution boards upstream power meters
- for protection against impact of direct or indirect lightning strikes in wide range of applications – houses, office or industrial buildings, resp. to sub- distribution boards in large buildings, for application in Germany



Product dimensions



Basic circuit diagram



Parameter name		Parameter value
Type of SPD		T1,T2,T3
Mounting		40 mm busbar system
Nominal voltage	U_n	230.00 V AC
Maximum operating voltage	U_c	255.00 V AC
Type of network		TN
Maximum overcurrent protection		160 A gL/gG
Short-circuit current rating	I_{SCCR}	25.0 kA
Total discharge current (10/350 µs)	$I_{Total(10/350)}$	22.50 kA
Lightning impulse current (10/350 µs)	I_{imp}	7.50 kA
Nominal discharge current (8/20 µs)	I_n	20.00 kA
Test voltage	U_{oc}	10.0 kV
Total discharge current (8/20 µs)	$I_{Total(8/20)}$	100.00 kA
Maximum discharge current (8/20 µs)	I_{max}	60.00 kA
Voltage protection level	U_p	1.50 kV
Response time	t_a	100 ns

TOV 5 s L-N	**335 V**
TOV characteristic (TOV 5 s)	**withstand**
TOV 120 min L-N	**440 V**
TOV characteristic (120 min)	**withstand**
Cross-section of connected conductors solid (min)	**1.00 mm^2**
Cross-section of connected conductors solid (max)	**35.00 mm^2**
Cross-section of connected conductors stranded (min)	**1.00 mm^2**
Cross-section of connected conductors stranded (max)	**25.00 mm^2**
Fault indication	**red indication field**
Degree of protection	**IP 20**
Range of ambient temperatures (min/max)	**-40 / 80 °C**
Humidity	**5 - 95 %**
According to standard	**EN 61643-11:2012, IEC 61643-11:2011**
ETIM Class	**EC000381**
Plug module	**FLP-ZP-7,5-VBH/0**
Customs tariff number	**85363090**
EAN	**8595090566212**
Order number	**A06621**